



TWINGUARD

**OAKFIELD MESH SYSTEMS
FOR SCHOOLS, PLAY AREAS, COMMERCIAL BUSINESS, RETAIL OUTLETS**

AVAILABLE FROM STOCK

Excellent rigid panel system with increased protection against cut through, ideal for use in schools, commercial outlets and a good alternative on industrial sites where other products are not suitable.

A rigid type system providing excellent visual appearance. Its aesthetic look is especially popular with Architects and Specifiers. Manufactured to BS: EN: 1722 Part 14 Cat 2 & 3.

ALSO AVAILABLE IN 8 x 6 x 8

Standard sizes

Heights above the standard range can be achieved using a multi-lift system.

Fence height (m)	Panel size H x W	Wire diameter H x V x H (mm)	Post centres (mm)	Post Section RHS	Clamp fixing
1.2	1233 x 2505	6*5*6mm	2520	60*40	40*5
1.8	1733 x 2505	6*5*6mm	2520	60*40	40*5
2.0	2033 x 2505	6*5*6mm	2520	60*40	40*5
2.4	2433 x 2505	6*5*6mm	2520	60*40	40*5
3.0	3033 x 2505	6*5*6mm	2520	60*40	40*5

Panels

Manufactured using 5mm vertical and 2no 6mm horizontal wires welded at each intersection creating a strong and durable panel. The mesh aperture consists of a 200 x 50mm mesh spacing providing excellent see through visibility!

Post system

Standard posts are manufactured from 60 x 40 x 2.5mm Rolled Hollow Section. All posts include threaded inserts, leaving a clean and flush design to the rear face.

PROFIX Twin is a specially designed clamping assembly that secures the panels in place.

Applications

The TWINGUARD system is suitable for most applications where general site demarcation is required. Typical examples: schools, public areas, industrial sites and retail outlets.

Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with rear hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions complete with anti-climb protection. See our gate range for further details.

